

Platform

0.91 m x 2.44 m low mount platform
 Side entry with inward swing gate
 Multiple function operation
 Full proportional drive joystick control with integral thumb steer switch
 Full proportional main boom and swing joystick control
 Variable speed dial control for telescope and platform rotate
 Selectable creep speed on drive / lift and swing functions
 1.83m articulating jib
 180 degree powered platform rotator
 Platform console machine status light panel¹
 Load sensing system
 AC cable to platform

Functional Equipment & Accessories

4 degree tilt alarm and indicator light
 18 x 24.5 foam filled lug tread tyres
 Fixed-width frame (extending axles not required)
 Load sensing boom function pump
 Lifting/tie down lugs
 Hour meter
 Ground control selector switch with key lock
 Platform tool tray
 12V DC auxiliary power

Available Options

0.91 m x 1.83 m low mount platform
 13 mm air line to platform
 Four wheel drive
 Oscillating front axle
 On-board 2500W Generator
 SkyPower™ Package 7,500 watt on-board generator
 SkyWelder® Package 250 amp welder in the platform³
 Nite-Bright® Package platform mounted lights⁴
 Tow Package⁵
 All motion alarm
 Alarm package⁶
 Light package⁷
 Head and tail lights
 Flashing amber beacon
 Plugs & Sockets
 Hostile environment package⁸
 Catalytic Purifier Muffler
 Corner storage tray

Power & Transmission

Deutz D2011L04 (47 kW) diesel engine
 Engine distress warning/shut down system²
 Gull-wing hoods
 Swing-out engine tray
 Spark arresting type muffler
 Control ADE™ - Advanced Design Electronics System
 Hydrostatic drive transmission
 Horn



¹ Provides indicator lights at platform control console for system distress, low fuel, tilt light, and foot switch status.

² Low oil pressure and high coolant temperature alarms with shut-down enabled/disabled by analyser.

³ Available when integrated with the SkyPower™ package.

⁴ Consists of six 40-watt lights, four turntable mounted lights and two platform mounted lights.

⁵ Available only with two wheel drive on models 400S and 460SJ.

⁶ Includes all-motion alarm and flashing amber beacon.

⁷ Includes platform mounted work lights and head & tail lights.

⁸ Includes console cover, boom wipers and cylinder bellows.

JLG Industries Inc.
 Polaris Avenue 63
 2132 JH Hoofddorp
 The Netherlands
 Tel: +31 (0)23 565 5665
 Fax: +31 (0)23 557 2493
 e-mail address: europe@jlg.com
www.jlgeurope.com
 An Oshkosh Corporation Company

860SJ

Platform height	26.21 m
Horizontal outreach	22.86 m
Swing (continuous)	360°
Platform capacity – unrestricted	230 kg
Platform rotator (hydraulic)	180°
Jib – overall length	1.83 m
Jib - range of articulation	130° (+70°/-60°)
A. Platform size	0.91 m x 2.44 m
B. Overall width	2.49 m
C. Tailswing (working condition)	1.42 m
D. Stowed height	3.05 m
E. Stowed length	12.19 m
F. Wheelbase	3.05 m
G. Ground clearance	0.30 m
Machine weight ¹	17,200 kg
Maximum ground bearing pressure	6.5 kg/cm ²
Drive speed 2WD	5.6 km/h
Drive speed 4WD	5.6 km/h
Gradeability 2WD	30%
Gradeability 4WD	45%
Tyres	18 x 24.5 Foam Filled
Axle oscillation	0.20 m
Turning radius – inside	3.66 m
Turning radius – outside	6.86 m
Diesel engine - Deutz D2011L04 ²	47 kW
Diesel engine (option) CAT 3.4	47 kW
Fuel tank capacity	117 L
Hydraulic system	235 L
Auxiliary power	12V DC

¹ Certain options or country standards may increase weight and/or dimensions.

² With EGR.

